



[DCA HOME](#) [ABOUT](#)

[BCIS Home](#) | [Log In](#) | [User Registration](#) | [Hot Topics](#) | [Submit Surcharge](#) | [Stats & Facts](#) | [Publications](#) | [FBC Staff](#)



Product Approval

USER: Public User

[Product Approval Menu](#) > [Product or Application Search](#) > [Application List](#) > **Application Detail**

- ▶ COMMUNITY PLANNING
- ▶ HOUSING & COMMUNITY DEVELOPMENT
- ▶ EMERGENCY MANAGEMENT
- ▶ OFFICE OF THE SECRETARY

FL #	FL2683-R2
Application Type	Revision
Code Version	2007
Application Status	Approved
Comments	
Archived	<input type="checkbox"/>
Product Manufacturer	American Shutter Systems Association, Inc
Address/Phone/Email	4268 Westroads Drive West Palm Beach, FL 33407 (561) 209-8263 bfeeley@easternmetal.com
Authorized Signature	Bill Feeley Irodriguez@easternmetal.com
Technical Representative	
Address/Phone/Email	
Quality Assurance Representative	
Address/Phone/Email	
Category	Shutters
Subcategory	Bahama
Compliance Method	Evaluation Report from a Florida Registered Florida Professional Engineer <input checked="" type="checkbox"/> Evaluation Report - Hardcopy Received
Florida Engineer or Architect Name who developed the Evaluation Report	Walter A. Tillit Jr.
Florida License	PE-44167
Quality Assurance Entity	National Accreditation and Management Institute
Quality Assurance Contract Expiration Date	12/31/2010
Validated By	John Henry Kampmann Jr.

Validation Checklist - Hardcopy Receipt

Certificate of Independence

[FL2683_R2_COI_Certificate_of_Independence](#)

Referenced Standard and Year (of Standard)

Standard

TAS 201, TAS 202, TAS 203

Equivalence of Product Standards Certified By

Sections from the Code

Product Approval Method

Method 1 Option D

Date Submitted

01/07/2009

Date Validated

03/09/2009

Date Pending FBC Approval

03/11/2009

Date Approved

04/07/2009

Summary of Products

FL #	Model, Number or Name	Description
2683.1	Extruded Bertha Bahama Shutter (Non-HVHZ) - Drawing#08-160	extruded aluminum blades retain aluminum frame and tracks, to provide protection.
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: Yes Design Pressure: N/A Other: Large missile. Max span is 42" x 96" at +75,-100 p.s.f. for single units depending on side bracket condition and 84" high x unlimited width for +62,-75 p.s.f. load depending on side bracket condition. See sheet 9 of installation drawings for other spans and pressures.		Installation Instructions FL2683_R2_II_Drawing_08-160 Verified By: American Test Lab Created by Independent Third Party Evaluation Reports FL2683_R2_AE_Product_Evaluation_0930.02.PDF Created by Independent Third Party

[Back](#)

[Next](#)

DCA Administration

Department of Community Affairs
Florida Building Code Online
Codes and Standards
 2555 Shumard Oak Boulevard
 Tallahassee, Florida 32399-2100
 (850) 487-1824, Fax (850) 414-8436

© 2000-2005 The State of Florida. All rights reserved. [Copyright and Disclaimer](#)

Product Approval Accepts:

